



Ful Flo Shutter Screen

Open Area for Mild Steel

casing diameter (in.)	6-5/8	8-5/8	10-3/4	12-3/4	14	16	18	20	22	24
casing diameter (mm)	168	219	273	324	356	406	457	508	559	610
holes / circle	6	8	8	8	8	10	12	14	14	16
holes / ft	72	96	96	96	96	120	144	168	168	192
holes / meter	236	315	315	315	315	394	472	551	551	630
slot size										
1/16" (Square inches per lineal foot)	7.3	9.8	15.8	15.8	15.8	19.7	23.6	27.6	27.6	31.5
1.59mm (Square centimeters per lineal meter)	155	206	333	333	333	417	500	583	583	667
3/32"	11.0	14.6	23.6	23.6	23.6	29.5	35.4	41.3	41.3	47.2
2.38 mm	232	310	500	500	500	625	750	875	875	1000
1/8"	14.6	19.5	31.5	31.5	31.5	39.4	47.2	55.1	55.1	63.0
3.18 mm	310	413	667	667	667	834	1000	1167	1167	1334
5/32"	18.3	24.4	39.4	39.4	39.4	49.2	59.1	68.9	68.9	78.8
3.97 mm	387	516	834	834	834	1042	1250	1459	1459	1667
3/16"	21.9	29.2	47.2	47.2	47.2	59.1	70.9	82.7	82.7	94.5
4.76 mm	464	619	1000	1000	1000	1250	1500	1750	1750	2001
1/4"	29.2	39.0	63.0	63.0	63.0	78.8	94.5	110.2	110.2	126.0
6.35 mm	619	826	1334	1667	1667	2001	2334	2667	2667	2667

